

watco® SAFETY DATA SHEET

Concrex Vertical Cold Cure - Resin

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Concrex Vertical Cold Cure - Resin
Product description : repair product
Product type : Solid.
UFI : J00W-60XQ-900C-GG2G

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses | |
|--|--------|
| Consumer Industrial Professional | |
| Uses advised against | Reason |
| None identified. | - |

1.3 Details of the supplier of the safety data sheet

Watco UK Limited
Eastgate Court
195-205 High Street
Guildford
Surrey
GU1 3EH
United Kingdom
Watco UK:
T: +44 (0) 1483 425000 (08:00 - 18:00)
F: +44 (0) 1483 428888

Watco FR
COLOFT - Espace de coworking
Arteparc
9 rue des Bouleaux
59810 Lesquin, France
Watco FR:
T: +33 (0) 3 20 52 77 77
F: +33 (0) 3 20 52 38 39
info@watco.fr
Watco BE:
T: +32 13 458 905

Watco GmbH DE
Kränkelsweg 14
41748 Viersen
Germany
Watco DE:
T: +49 (0) 21 62 530 17 17(08:00 - 17:00)
F: +49 (0) 21 62 530 17 77
info@watco.de
Watco AT:
T: +43 1 310 09 10

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.4 Emergency telephone number

[National advisory body/Poison Centre](#)

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798
Great Britain

Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

[Classification according to UK CLP/GHS](#)

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

[Precautionary statements](#)

General : Not applicable.

Prevention : P280 - Wear protective gloves. Wear eye or face protection.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
benzyl alcohol

Supplemental label elements : EUH205 - Contains epoxy constituents. May produce an allergic reaction.

Supplemental label elements : Detergents - Regulation (EC) No 907/2006 : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Concrex Vertical Cold Cure - Resin

SECTION 2: Hazards identification**Special packaging requirements**

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers | % | Classification | Type |
|--|--|-----------|--|------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2 | ≥10 - ≤16 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 | [1] |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5 | ≤8,3 | Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411 | [1] |
| benzyl alcohol | REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5 | ≤3 | Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319 Skin Sens. 1B, H317 | [1] |
| | | | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Concrex Vertical Cold Cure - Resin

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|--|------|-----------------------|-------------------------|--------------------------------|----------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | DNEL | Short term Dermal | 83 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 104,15 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 29,39 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 62,5 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Long term Inhalation | 8,7 mg/m ³ | General population [Consumers] | Systemic |
| | DNEL | Long term Oral | 6,25 mg/kg bw/day | General population [Consumers] | Systemic |
| benzyl alcohol | DNEL | Short term Dermal | 47 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 450 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 9,5 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 90 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Dermal | 28,5 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Short term Inhalation | 40,55 mg/m ³ | General population [Consumers] | Systemic |

SECTION 8: Exposure controls/personal protection

| | | | | | |
|--|------|-----------------------|------------------------|--------------------------------|----------|
| | DNEL | Short term Oral | 25 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Long term Dermal | 5,7 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Long term Inhalation | 8,11 mg/m ³ | General population [Consumers] | Systemic |
| | DNEL | Long term Oral | 5 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Short term Dermal | 20 mg/kg | General population | Systemic |
| | DNEL | Long term Oral | 4 mg/kg | General population | Systemic |
| | DNEL | Long term Dermal | 8 mg/kg | Workers | Systemic |
| | DNEL | Short term Oral | 20 mg/kg | General population | Systemic |
| | DNEL | Long term Dermal | 4 mg/kg | General population | Systemic |
| | DNEL | Short term Inhalation | 27 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 5,4 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 22 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 110 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Dermal | 40 mg/kg | Workers | Systemic |

PNECs

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|--|------------------------|------------------|--------------------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | Fresh water | 0,003 mg/l | - |
| | Marine water | 0,0003 mg/l | - |
| benzyl alcohol | Sewage Treatment Plant | 10 mg/l | - |
| | Fresh water sediment | 0,294 mg/kg dwt | - |
| | Marine water sediment | 0,0294 mg/kg dwt | - |
| | Soil | 0,237 mg/kg dwt | - |
| | Fresh water | 1 mg/l | Assessment Factors |
| | Marine | 0,1 mg/l | Assessment Factors |
| | Fresh water sediment | 5,27 mg/kg | Assessment Factors |
| | Marine water sediment | 0,527 mg/kg | Assessment Factors |
| | Soil | 0,456 mg/kg | Assessment Factors |
| | Sewage Treatment Plant | 39 mg/l | Assessment Factors |
| | Fresh water | 2,3 mg/l | - |
| | Sewage Treatment Plant | 39 mg/l | - |
| | Fresh water sediment | 5,27 mg/kg | - |
| | Soil | 0,456 mg/kg | - |
| | Marine water sediment | 0,527 mg/kg | - |
| | Fresh water | 1 mg/l | - |
| | Marine water | 0,1 mg/l | - |

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

SECTION 8: Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber gloves

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: disposable particulate mask (EN 140)

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state : Solid.
Colour : Yellowish. Yellow.
Odour : Mild. [Slight]

SECTION 9: Physical and chemical properties

| | |
|--|---|
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : Not relevant due to nature of the product. |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosion limit | : Not applicable. |
| Flash point | : Closed cup: >100°C (>212°F) [Literature] |
| Auto-ignition temperature | : Not relevant due to nature of the product. |
| Decomposition temperature | : Not available. |
| pH | : Not applicable. |
| pH : Justification | : Product is non-soluble (in water). |
| Viscosity | : Dynamic (room temperature): >5000 mPa·s [Literature] Kinematic (room temperature): 4284 mm ² /s [calculated.] Kinematic (40°C): Not available. |
| Solubility(ies) | : |

| Media | Result |
|------------|-------------|
| cold water | Not soluble |
| hot water | Not soluble |

| | |
|--|---|
| Solubility in water | : Not available. |
| Miscible with water | : No. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapour pressure | : <0,0013 kPa (<0,01 mm Hg) [calculated.] |
| Evaporation rate | : Not available. |
| Relative density | : 1,16 |
| Density | : 1,167 g/cm ³ [20°C (68°F)] [DIN 53217] |
| Vapour density | : Not applicable. |
| Explosive properties | : Not available. |
| Oxidising properties | : Not available. |
| Particle characteristics | |
| Median particle size | : Not available. |

SECTION 10: Stability and reactivity

| | |
|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : No specific data. |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|---------|------------|----------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | LD50 Dermal | Rabbit | 20 g/kg | - |
| benzyl alcohol | LC50 Inhalation Dusts and mists | Rat | 4,178 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 2000 mg/kg | - |
| | LD50 Oral | Rat | 1620 mg/kg | - |
| | LD50 Oral | Rat | 1660 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Concrex Vertical Cold Cure - Resin | 70588,2 | N/A | N/A | N/A | 245,8 |
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | N/A | 20000 | N/A | N/A | N/A |
| benzyl alcohol | 1200 | N/A | N/A | N/A | 4,178 |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|--------------------------|-------------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | Eyes - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | Skin - Erythema/Eschar | Rabbit | 0,7 | 4 hours | 72 hours |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 microliters | - |
| benzyl alcohol | Eyes - Irritant | Rabbit | - | - | - |
| | Skin - Moderate irritant | Pig | - | 100 Percent | - |

Skin : Causes skin irritation.

Eyes : Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|--|-------------------|---------------------|----------------------------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | skin | Guinea pig | Sensitising |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | skin skin | Mouse Guinea pig | Sensitising Sensitising |

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

SECTION 11: Toxicological information

| Product/ingredient name | Test | Experiment | Result |
|--|----------|---|----------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | OECD 476 | Experiment: In vitro Subject: Mammalian-Animal | Positive |
| | OECD 471 | Subject: Bacteria | Positive |
| | OECD 474 | Subject: Mammalian-Animal | Negative |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|----------------------|---------|------|----------------------------|
| benzyl alcohol | Negative - Oral - TD | Rat | - | 103 weeks; 5 days per week |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species | Dose | Exposure |
|--|-------------------|-----------|---------------------|---------|-----------------|----------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | Negative | - | - | Rat | Oral: 540 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---|-----------------|------------|--------------------------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane | Positive - Dermal | Rabbit | 300 mg/kg | 1 days per week |
| | Positive - Oral | Rabbit | 180 mg/kg | 1 days per week |
| | Positive - Oral | Rat | 180 mg/kg | 1 days per week |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | Negative - Route of exposure unreported | Rabbit - Female | >300 mg/kg | - |
| | Positive - Dermal | Rabbit | 300 mg/kg | 6 hours; 7 days per week |
| | Positive - Dermal | Rabbit | 100 mg/kg | 6 hours; 7 days per week |
| benzyl alcohol | Negative - Route of exposure unreported | Mouse - Female | 550 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

SECTION 11: Toxicological information

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure | |
|--|-----------------------|------------------------------------|--|----------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | Acute EC50 1,8 mg/l | Algae | 72 hours | |
| | Acute EC50 2 mg/l | Daphnia spec. | 24 hours | |
| | Acute EC50 1,6 mg/l | Daphnia spec. | 48 hours | |
| | Acute IC50 >100 mg/l | Bacteria | 3 hours | |
| | Acute LC50 0,55 mg/l | Fish | 96 hours | |
| | Acute LC50 2 mg/l | Fish | 96 hours | |
| | Chronic NOEC 0,3 mg/l | Daphnia spec. | 21 days | |
| | benzyl alcohol | Acute EC50 770 mg/l | Algae | 72 hours |
| | | Acute LC50 646 mg/l | Fish - <i>Leuciscus idus</i> | 48 hours |
| | | Acute LC50 460000 µg/l Fresh water | Fish - Fathead minnow - <i>Pimephales promelas</i> - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Acute NOEC 310 mg/l | Algae | 72 hours | |

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

SECTION 12: Ecological information**12.2 Persistence and degradability**

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|----------------|---|--------|----------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | OECD 301B | 6 to 12 % - Not readily - 28 days | - | - |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | OECD 301B | 16 % - Not readily - 28 days | - | - |
| benzyl alcohol | - OECD 301A | 0 % - Not readily - 28 days 96 % - Readily - 21 days | - - | - - |

Conclusion/Summary : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | - | - | Not readily |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | - | - | Not readily |
| benzyl alcohol | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|---------|-----------|
| 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane | 3,84 | 3 to 31 | Low |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | 2,7 | 150 | Low |
| benzyl alcohol | 0,87 | - | Low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods**Product**

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Waste catalogue

| Waste code | Waste designation |
|------------|---|
| 20 01 27* | paint, inks, adhesives and resins containing hazardous substances |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |
| | | | | |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Other EU regulations

VOC : Exempt

VOC for Ready-for-Use Mixture : Exempt

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

CN code : 3214 10 10 00

Inventory list

Australia : Not determined.

Canada : Not determined.

China : Not determined.

SECTION 15: Regulatory information

| | |
|--|--|
| Eurasian Economic Union | : Russian Federation inventory: Not determined. |
| Japan | : Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. |
| New Zealand | : Not determined. |
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : All components are listed or exempted. |
| Thailand | : Not determined. |
| Turkey | : All components are listed or exempted. |
| United States | : Not determined. |
| Viet Nam | : Not determined. |
| 15.2 Chemical safety assessment | : This product contains substances for which Chemical Safety Assessments are still required. |

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

| | |
|-----------------------------------|--|
| Abbreviations and acronyms | : ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative |
|-----------------------------------|--|

Procedure used to derive the classification

| Classification | Justification |
|-------------------------|--------------------|
| Skin Irrit. 2, H315 | Calculation method |
| Eye Irrit. 2, H319 | Calculation method |
| Skin Sens. 1, H317 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Full text of classifications

| | |
|-------------------|---|
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| Skin Sens. 1B | SKIN SENSITISATION - Category 1B |

Date of printing : 5/09/2024

Date of issue/ Date of revision : 5/09/2024

SECTION 16: Other information

Date of previous issue : 5/09/2024

Version : 4

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.