

# atco SAFETY DATA SHEET

Powerfloat Sealer Matt Anti Slip - Resin

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Powerfloat Sealer Matt Anti Slip - Resin

Product description : Resin
Product type : Liquid.

UFI : 2S90-K0AY-X00M-THNW

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Consumer Industrial Professional	

Uses advised against	Reason
None identified.	-

#### 1.3 Details of the supplier of the safety data sheet

Watco UK Limited Eastgate Court 195-205 High Street Guildford Surrey

GU13EH

Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00)

Fax no.: +44 (0) 1483 428888

e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

#### 1.4 Emergency telephone number

#### **National advisory body/Poison Centre**

Telephone number United Kingdom: : 809 2166

Northern Ireland Available 8am to 10pm 7 days per week

**Supplier** 

Telephone number United Kingdom: : +353 19014670

Northern Ireland

Hours of operation : 24 / 7

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 1/15

## **SECTION 2: Hazards identification**

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

General : P103 - Read carefully and follow all instructions.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: EUH210 - Safety data sheet available on request.

Supplemental label elements : Detergents - Regulation (EC) No

907/2006

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

**Special packaging requirements** 

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture United Kingdom: Northern Ireland

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤10	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9	≤3	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1620 mg/kg ATE [Inhalation	[1]

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 2/15

Powerfloat Sealer Matt Anti Slip - Resin

## **SECTION 3: Composition/information on ingredients**

CAS: 100-51-6 Index: 603-057-0	0-5		(dusts and mists)] = 4,178 mg/l	
	th	tee Section 16 for the full text of the H tatements declared bove.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision: 25/01/2023Date of previous issue: No previous validationVersion: 43/15

## **SECTION 5: Firefighting measures**

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information

: No unusual hazard if involved in a fire.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

nitrogen oxides

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8).

Date of issue/Date of revision: 25/01/2023Date of previous issue: No previous validationVersion: 4

Powerfloat Sealer Matt Anti Slip - Resin

## SECTION 7: Handling and storage

#### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

# solutions

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

**United Kingdom: Northern Ireland** 

Product/ingredient name	Exposure limit values
1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 560 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 8 hours. TWA: 100 ppm 8 hours.

#### **Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
1-methoxy-2-propanol	DNEL	Short term Inhalation	553,5 mg/ m³	Workers	Local
	DNEL	Long term Inhalation	369 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	50,6 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	43,9 mg/m³	General population [Consumers]	Systemic

Date of issue/Date of revision : 25/01/2023 5/15 Date of previous issue Version: 4 : No previous validation

# **SECTION 8: Exposure controls/personal protection**

<u>-</u>					
	DNEL	Long term Dermal	18,1 mg/ kg bw/day	General population	Systemic
				[Consumers]	
	DNEL	Long term Oral	3,3 mg/kg	General	Systemic
			bw/day	population	
			_	[Consumers]	
benzyl alcohol	DNEL	Short term Dermal	47 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term	450 mg/m <sup>3</sup>	Workers	Systemic
	האודו	Inhalation	0.5	\\/ = =	0 1 : -
	DNEL	Long term Dermal	9,5 mg/kg	Workers	Systemic
	DNE	Langutano	bw/day	\\/amlcama	Cyatamia
	DNEL	Long term Inhalation	90 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	28,5 mg/	General	Systemic
	DIVEL	Short term Dermai	kg bw/day	population	Systernic
			ng bw/day	[Consumers]	
	DNEL	Short term	40,55 mg/	General	Systemic
	DIVLE	Inhalation	m <sup>3</sup>	population	Cyclonic
				[Consumers]	
	DNEL	Short term Oral	25 mg/kg	General	Systemic
			bw/day	population	,
			, ,	[Consumers]	
	DNEL	Long term Dermal	5,7 mg/kg	General	Systemic
			bw/day	population	•
				[Consumers]	
	DNEL	Long term	8,11 mg/m <sup>3</sup>		Systemic
		Inhalation		population	
		_	_	[Consumers]	
	DNEL	Long term Oral	5 mg/kg	General	Systemic
			bw/day	population	
	האודו	Ob 4 4 D	00 //	[Consumers]	0 1 : -
	DNEL	Short term Dermal	20 mg/kg	General	Systemic
	חאבו	Long torm Oral	4 malka	population	Systemic
	DNEL	Long term Oral	4 mg/kg	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg	General	Systemic
		2.7011 101111 0141		population	
	DNEL	Long term Dermal	4 mg/kg	General	Systemic
				population	,
	DNEL	Short term	27 mg/m³	General	Systemic
		Inhalation	J.	population	
	DNEL	Long term	5,4 mg/m³	General	Systemic
		Inhalation	_	population	
	DNEL	Long term	22 mg/m³	Workers	Systemic
		Inhalation			
	DNEL	Short term	110 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Short term Dermal	40 mg/kg	Workers	Systemic

### **PNECs**

Product/ingredient name	Compartment Detail	Value	<b>Method Detail</b>
1-methoxy-2-propanol	Fresh water	10 mg/l	-
	Fresh water sediment	41,6 mg/l	-
	Marine water sediment	4,17 mg/l	-
	Soil	2,47 mg/l	-
	Sewage Treatment Plant	100 mg/l	-
benzyl alcohol	Fresh water	1 mg/l	Assessment Factors
·	Marine	0,1 mg/l	Assessment Factors
	Fresh water sediment	5,27 mg/kg	Assessment Factors

Date of issue/Date of revision: 25/01/2023Date of previous issue: No previous validationVersion: 46/15

## **SECTION 8: Exposure controls/personal protection**

Marine water sedime	ent 0,527 mg/kg	Assessment Factors
Soil	0,456 mg/kg	Assessment Factors
Sewage Treatment	39 mg/l	Assessment Factors
Plant		
Fresh water	2,3 mg/l	-
Sewage Treatment	39 mg/l	-
Plant		
Fresh water sedimer	nt 5,27 mg/kg	-
Soil	0,456 mg/kg	-
Marine water sedime	ent 0,527 mg/kg	-
Fresh water	1 mg/l	-
Marine water	0,1 mg/l	-

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

#### **Skin protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): nitrile rubber

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 7/15

## SECTION 8: Exposure controls/personal protection

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: If ventilation is inadequate, use respirator that will protect against organic vapour and dust/mist.

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Physical state** : Liquid. [Viscous liquid.]

Colour : White.

**Odour** : Not available. **Odour threshold** : Not available.

Melting point/freezing point

**Initial boiling point and** 

boiling range

: 0°C [Literature]

: >100°C (>212°F) [Literature]

Flammability (solid, gas) : Non-flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge, heat and shocks and mechanical impacts.

Nonflammable, but will burn on prolonged exposure to flame or high

temperature.

Lower and upper explosion

limit

: Not available.

Flash point : Not relevant due to nature of the product. **Auto-ignition temperature** : Not relevant due to nature of the product.

**Decomposition temperature** 

: Not available.

: 6 to 8 [Conc. (% w/w): 100%] [Literature] pН

pH: Justification : Not available.

**Viscosity** Dynamic: 8600 mPa·s [DIN EN ISO 3219]

Solubility(ies)

Media	Result	
cold water	Soluble	
hot water	Soluble	
methanol	Very slightly soluble	
acetone	Very slightly soluble	

: Not available. Solubility in water

Miscible with water : Yes.

Partition coefficient: n-octanol/ : Not applicable.

water

: 2,3 kPa (17,25 mm Hg) [Literature] Vapour pressure

: <1 (butyl acetate = 1) **Evaporation rate** 

**Relative density** : Not available.

: 1,1 to 1,16 g/cm<sup>3</sup> [20°C (68°F)] [DIN 53217] **Density** 

: >1 [Air = 1] Vapour density

: Non-explosive in the presence of the following materials or conditions: open **Explosive properties** 

flames, sparks and static discharge and heat.

No unusual hazard if involved in a fire.

Date of issue/Date of revision : 25/01/2023 Date of previous issue 8/15 Version: 4 : No previous validation

Powerfloat Sealer Matt Anti Slip - Resin

## SECTION 9: Physical and chemical properties

**Oxidising properties** 

: Not available.

**Particle characteristics** 

Median particle size : Not applicable.

## **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

**10.5 Incompatible materials**: No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1-methoxy-2-propanol	LC50 Inhalation Vapour	Rat	30,02 mg/l	4 hours
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Mouse	11700 mg/kg	-
	LD50 Oral	Rat - Male,	4016 mg/kg	-
		Female		
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	4,178 mg/l	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1620 mg/kg	-
	LD50 Oral	Rat	1660 mg/kg	-

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	
benzyl alcohol	1620	N/A	N/A	N/A	4,178

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Eyes - Irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Pig	-	100 Percent	-

#### **Conclusion/Summary**

Skin
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Respiratory
 Based on available data, the classification criteria are not met.

**Sensitisation** 

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 9/15

Powerfloat Sealer Matt Anti Slip - Resin

## **SECTION 11: Toxicological information**

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

**Mutagenicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Carcinogenicity** 

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	Negative - Oral - TD	Rat	-	103 weeks; 5 days per week

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

**Reproductive toxicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Teratogenicity** 

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	Negative - Route of exposure unreported	Mouse - Female	550 mg/kg	-

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-methoxy-2-propanol	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on likely routes

of exposure

: Routes of entry anticipated: Oral, Inhalation. Routes of entry not anticipated: Dermal.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

**Long term exposure** 

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 10/15

Powerfloat Sealer Matt Anti Slip - Resin

## **SECTION 11: Toxicological information**

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1-methoxy-2-propanol	Acute EC50 >1000 mg/l	Algae - Selenastrum capricomutum	7 days
	Acute EC50 23300 mg/l	Daphnia spec.	96 hours
	Acute LC50 6812 mg/l Fresh water	Fish	96 hours
benzyl alcohol	Acute EC50 770 mg/l	Algae	72 hours
	Acute LC50 646 mg/l	Fish - Leuciscus idus	48 hours
	Acute LC50 460000 μg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute NOEC 310 mg/l	Algae	72 hours

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1-methoxy-2-propanol	OECD 301E	96 % - Readily - 28 days	-	-
	OECD 301C	88 to 92 % - Readily - 28 days	-	-
	-	>90 % - Readily - 5 days	1,95 gO <sub>2</sub> /g	-
			ThOD	
benzyl alcohol	OECD 301A	96 % - Readily - 21 days	-	-

**Conclusion/Summary**: According to EC criteria: Expected to be inherently biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-methoxy-2-propanol	Fresh water <28 days, 5 to 25°C		Readily
benzyl alcohol	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1-methoxy-2-propanol	<1	<100	low
benzyl alcohol	0,87	-	low

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 11/15

Powerfloat Sealer Matt Anti Slip - Resin

## **SECTION 12: Ecological information**

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### **European waste catalogue (EWC)**

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

#### **Special precautions**

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 12/15

Powerfloat Sealer Matt Anti Slip - Resin							
SECTION 14: Transport information							
14.5 Environmental hazards	No.	No.	No.	No.			

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions**: Not applicable. on the manufacture, placing on the market and use of certain dangerous substances,

#### Other EU regulations

mixtures and articles

VOC

: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** 

: IIA/j. Two-pack reactive performance coatings for specific end use such as floors. EU limit value for this product : 140g/l (2010.) This product contains a maximum of 50 g/l VOC.

**Industrial emissions** (integrated pollution prevention and control) - : Not listed

**Industrial emissions** (integrated pollution prevention and control) - : Not listed

Water

Air

Ozone depleting substances (1005/2009/EC)

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

Date of issue/Date of revision : 25/01/2023 Version: 4 13/15 Date of previous issue : No previous validation

Powerfloat Sealer Matt Anti Slip - Resin

## **SECTION 15: Regulatory information**

#### **United Kingdom: Northern Ireland**

**References**: EH40/2005 Workplace exposure limits

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2020/878

REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council

Directive 89/686/EEC

#### **International regulations**

#### **Stockholm Convention on Persistent Organic Pollutants**

List name	Ingredient name	Status
Not listed.		

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

List name	Ingredient name	Status
Not listed.		

**CN code** : 3209 90 00 00

**Inventory list** 

Australia : Not determined.
Canada : Not determined.
China : Not determined.

**Eurasian Economic Union**: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : Not determined.

**Philippines** : At least one component is not listed.

Republic of Korea : Not determined.
Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.
United States : Not determined.
Viet Nam : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Date of issue/Date of revision : 25/01/2023 Date of previous issue : No previous validation Version : 4 14/15

#### **SECTION 16: Other information**

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

#### Full text of abbreviated H statements

#### **United Kingdom: Northern Ireland**

Full text of abbreviated H

statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed. H319 Causes serious eve irri

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Full text of classifications
[CLP/GHS]

Acute Tox. 4 ACUTE TOXICITY - Category 4

Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -

Category 3

Date of printing

Date of issue/ Date of

Date of previous issue

revision

: 15/03/2023: 25/01/2023

: No previous validation

Version : 4

**Notice to reader** 

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.