

Watco Tactile Plates

Tough, GRP tiles with raised profiles to warn pedestrians of a change in elevation or a hazard ahead



Watco Tactile Plates are available in two colours and three different styles:

Corduroy Version: Warns visually impaired people of the presence of hazards such as stairs or pedestrian crossings.

Blister Onstreet Version: – Indicates the edge of a footway near a crossing. Designed with 36 blisters in regular rows and columns on each tile, it helps prevent the visually impaired from inadvertently walking into a vehicular route.

Blister Offstreet Version: The blisters on this tile run parallel in one direction, but are irregular in the other direction. This indicates that movement in one direction is safe, and is ideal for train or light rail platforms.




Areas of use:

- Regulation compliant for use near steps and crossings
- For more detailed guidance on where to use tactile paving, please see the document on the use of tactile paving surfaces at www.dft.gov.uk

Features:

- The surface is coated with aluminium oxide grit for slip and high wear resistance
- Plates are glued and screwed to the existing substrate to avoid costly excavation
- Only 4mm thick
- Virtually indestructible Glass Reinforced Plastic (GRP)
- Rot resistant

Colours



Buff



Tile red

(Only available for Blister Onstreet version)

*Samples are available on request.

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Watco Tactile Plates**.

Call our expert team on: 01483 418 418 (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Watco Tactile Plates

Tough, GRP tiles with raised profiles to warn pedestrians of a change in elevation or a hazard ahead

Specification

Composition	GRP (Glass Reinforced Plastic) coated with aluminium oxide grit.
Suitable for	Concrete, stone and asphalt.
Usage Interior/Exterior	Exterior.
Size	400mm x 400mm
Thickness	4mm
Availability	Single units or packs of five.
Correct uses	Use Tile Red Tactile Plates for Controlled crossings, i.e: Zebras, Pelicans, Puffins, Toucans, Traffic signal junctions with pedestrian phases. Use Buff Tactile Plates for Uncontrolled crossings, i.e: Side road crossings, Busy crossovers (vehicle crossings), Crossings away from junctions, Kerb to kerb flat top road humps, Signal controlled junctions without pedestrian phases (traffic lights), including those where studs indicating a pedestrian crossing place is provided.

Fixing

Watco Tactile Plates can be glued or screw fixed to the substrate. If the substrate is reasonably smooth and even, Watco GRP Polyurethane Adhesive can be used. The substrate should be clean and dry. A mechanical fixing is not generally required. If the substrate is uneven, Watco Adhesive Mastic can be used as a gap filling adhesive. When using Watco Adhesive Mastic we recommended that a screw fixing is made in each corner of each tile. The plate is easily drilled and any type of screw and Rawlplug fixing can be used which best suits the substrate. Watco Adhesive Mastic and screw fixings are recommended if the substrate is damp, very cold, contaminated or in generally poor condition.

Watco Adhesive Mastic 310ml tube & Watco GRP Polyurethane Adhesive

295ml tube – Both tubes fit into a standard skeleton gun (also available from Watco). A tube of each adhesive should be sufficient for fixing 7 -10 Watco Tactile Plates depending on the substrate.

