

Bio-D

Removes grease and oil from painted or bare concrete



Watco Bio-D is unusual since it attacks heavy oil and grease yet it is a water based, biodegradable formulation. It has been specially formulated to remove grease and oil from previously painted or bare concrete where sensitivity to solvents from traditional degreasants may be a problem. Bio-D will remove oil and grease contamination without softening or bleaching the existing coating, unlike most solvent based degreasers. This water based and virtually odourless degreaser is safe and easy to use in concentrate form for the removal of heavy contamination, or diluted with water for light-medium dirt deposits.



Areas of use:

- For preparation of dirty, oily floors prior to painting
- Dilute with water for use as a maintained degreaser
- Inside or outside

Features:

- This powerful degreaser will not damage or soften previously painted or sealed surfaces
- Unique water based formulation
- Odourless – ideal for use in sensitive areas or where ventilation is limited
- Biodegradable
- Economical – may be diluted or used neat
- Only one application generally needed
- Easy to use

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Bio-D**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Bio-D

Removes grease and oil from painted or bare concrete

1 Mixing

Give the container a shake prior to application.

2 Application

Floor preparation prior to painting:

Floors with heavy contamination – should be reasonably dry for Bio-D to be most effective. Brush in undiluted Watco Bio-D with a stiff broom, scrub and leave it for at least 15 minutes to allow it to penetrate and to lift the contamination out of the surface. Scrub the floor again with a stiff broom or a mechanical scrubber to loosen the dirt deposits. Rinse with clean, cold water preferably whilst continuing to scrub. If further applications are required, the floor should be reasonably dry before repeating the process.

Floors with light-medium contamination – as above but Bio-D may be diluted.

Floor maintenance: Bio-D can be diluted with up to 10 times water for cleaning existing painted or bare floor surfaces.

3 Safety

Material Safety Data Sheets are available.

4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale. The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Bio-D

Removes grease and oil from painted or bare concrete

Specification

Composition	Water based degreaser.
Number of Components	1
Number of Applications	Usually 1.
Usage Interior/Exterior	Exterior & interior.
Application Tools	Soft broom or scrubbing machine for painted surfaces, stiff broom for bare concrete.
Overcoat Times	As soon as the surface has thoroughly dried.
Suitable For	Concrete, sand and cement screed, asphalt, bricks, blockwork.
Pack Size	5L & 25L
Shelf Life	24 months in unopened container.
Storage	Do not allow to freeze.
Coverage	Approx. 20m ² per 5 litres and 100m ² per 25 litres for heavy contamination. Can be diluted with up to five times water for lighter contamination prior to painting, or up to 10 times with water for cleaning and maintaining existing painted surfaces.
Cleaning Tools	Water.
Principle Limitations Please contact us regarding applications not described here.	Once Bio-D has been used to remove oil or grease it must not be allowed to enter sewers and should never be allowed to enter rainwater drains or open water courses. In such cases it should be removed from the floor by the use of a squeegee in conjunction with absorbent material (sawdust or sand) and disposed of as chemical waste.