

WEATHERGUARD

A tough, flexible and long term decorative coating for walls



AREAS OF USE

- Weatherproofs and protects exposed or painted masonry

FEATURES

- Life expectancy of at least 10 years
- Weather and waterproof
- Impact resistant
- Allows for considerable surface movement
- Will not support fungal or algae growth

DESCRIPTION

Watco Weatherguard is formulated to give an impermeable protective coating that will withstand extremes of temperature without softening or hardening. Extremely tough and flexible, it can be applied to almost all surfaces. The cured film will stretch up to twice its original surface area without detrimental effect and will cope with any movement caused by temperature change, settlement or flexing. Controlled vapour permeability minimises build-up of condensation and loss of film adhesion. Watco Weatherguard will reduce solar heat gain as it will reflect 85% of infra-red radiation.

SPECIFICATION

Composition	Water based acrylic polymer.	Drying Time (for overcoating)	Touch dry: 4-6 hours at 20°C. Lower temperatures or damp humid conditions will extend the drying time.
Number of Components	1	Cleaning Tools	Wash brushes or rollers with water immediately after use.
Finish	Matt or low sheen depending on substrate.	Shelf Life	24 months in unopened container.
Primer Required	No.	Storage	Protect from frost. Do not allow to freeze.
Number of Coats	1	Safety	Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.
Usage Interior/ Exterior	Exterior.	Principle Limitations	Do not apply in damp, humid conditions or if rain is forecast within 24 hours, or at temperatures below 5°C.
Application Tools	Medium pile roller or brush.		
Suitable For	Brick, masonry, stone, rendered and other cementitious surfaces.		
Pack Size	10L		
Coverage	Generally 40m ² per 10L per coat depending on the substrate.		

COLOURS

White
Cream

Samples are available on request.
While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

PREPARATION & APPLICATION

SURFACE PREPARATION

The surface to which Watco Weatherguard is to be applied should be clean, dry and free of any loose material and contamination. Use a fungicide to remove any fungi, mildew or moss, etc. Scrape off any loose paint. Existing hard smooth, glossy paint should be lightly sanded to provide a key. Wash with a detergent solution, rinse with water and allow to dry. Make good any minor defects with an external filler or sand/cement mix.

Wooden Surfaces – All bare wooden surfaces should be clean and dry. Do not apply to door or window frames or previously painted wood, unless all traces of old paint has been removed.

STIRRING

Do not stir, but blend in any thin liquid that may have appeared on the surface of the product.

APPLICATION

Apply Watco Weatherguard by brush or roller in one direction at the rate of 4m² per litre, allowing the first coat to dry before applying the second coat.



WATCO.CO.UK